

Next Generation Solar [®] **Photovoltaics Canada** National Scientific Conference

Université de Montréal Contributed Talk May 2014







May 14 to 16, 2014

Erik Janssen, м.а.sc.

Toronto and Region Conservation Authority Sustainable Technology Evaluation Program

Implementing IEC 61853 in Canada: A Study of Common PV Operating Conditions in Ontario





Overview

- o Introduction to STEP
- o Background
 - o IEC 61853
- o Aims
 - Evaluating IEC 61853 Testing Points
- o Method
 - PVSyst Simulations
- o Results
- Conclusion





May 14 to 16, 2014

Introduction to STEP

- Sustainable Technology Evaluation Program
- o Branch of TRCA
- Industry-level research supporting the dissemination of sustainable technologies in Ontario and beyond
- Funded by government, NGOs, industry and academic partnerships
- o Education, Outreach, Training





May 14

Introduction to STEP















Background – IEC 61853

- Common Rating
 Standard IEC 61215
 (and IEC 61646)
 - STC Conditions 25
 °C; AM 1.5; 1000
 W/m², etc.
 - P_{MAX}, V_{OC}, I_{SC}, Temp Coeffs., NOCT

	ELECTRICAL DATA @ STC	REC215PE (BLK)
	Peak Power Watts-P _{MAX} (Wp)	215
	Watt Class Tolerance - P _{TOL} (W)	0/+5
	Watt Class Tolerance - P _{TOL} (%)	0/+2
	$Maximum Power Voltage-V_{_{MPP}}(V)$	28.3
	Maximum Power Current - I _{MPP} (A)	7.6
	Open Circuit Voltage - V _{oc} (V)	36.3
	Short Circuit Current - I _{sc} (A)	8.1
)	Module Efficiency (%)	13.0
	Values at Standard Test Conditions STC (Air	Mass AM 1.5, Irra

- To predict energy (profit) yield simulate
 From limited data, assumptions are made
- regarding the performance at different:
 - o Irradiance levels
 - Module temperatures
 - o Incidence angles
 - Wind speeds (thermal model)^{Université} m de Montréal
 - Variations in spectrums



Background – IEC 61853

Effect of irradiance level on efficiency [2]

Relative normalized irradiance-dependent efficiency n_rel(G)





Background

- o IEC 61853
- Addresses these assumptions via additional performance measurements
- o Introduces matrix of 23 testing points
- Suitable for Ontario/Canadian climate?





Aims

- STEP was funded by NRCan to complete multiphase study concerning development of IEC 61853 for Ontario and Canadian climate
- 1st Phase: Compare Ontario/Canadian climate with IEC 61853 test points –are they suitable?
- STEP commissioned SAIC (now Leidos) to complete that phase of the study
- STEP focus thus far has been on implementing monitoring infrastructure for tracing IV curves according to test matrix and acquiring data





Evaluating IEC 61853

- Representative 100 kW ground mount and roof mount PV system simulated in PVSyst for 13 different locations in Ontario
- Climate data from Canadian Weather for Energy Calculation (CWEC) data files
- Output: hourly data for plane of array solar irradiance, module temperature and array energy produced over TMY







Results – Ground Mount

Operating Condition Frequency of Occurence: Ground Installs (Ontario)



de Montréal



Results – Roof Mount





Results - Overall





Results

Over 26 (13 sites x 2 installations) simulations: Ο

- 23% of all energy is produced below 15 °C Ο
- 10% of energy is produced below 5 °C Ο
- Several high temperature points never 0 occurred
- Worst disagreement was for Timmins Ο
 - 33% of energy produced is below 15 °C Ο
- Require new test points at 0 °C Ο
- Some high temperature points unnecessary Ο

	Irradiance								
			100 W/m²	200 W/m²	400 W/m²	600 W/m²	800 W/m²	1,000 W/m²	1,100 W/m²
	Module Temperature	75°C				15	11	7	3
		50°C		21	18	14	10	6	2
		25°C	23	20	17	13	9	5	1
		15°C	22	19	16	12	8	4	
		0°C	28	27	26	25	24		
		Not required		Additions				Optional	



Conclusion

- IEC 61853 allows for more accurate energy yield predictions via expanded testing
- Investigated if testing points are suitable for Ontario
- o Simulated representative PV installations
- 23% of energy produced below testing matrix points
- Suggested changes to IEC 61853 matrix for Ontario climate
- Future work use experimental data to inform development of performance metrics from results of IEC 61853-1 and -2





Ο

Acknowledgments

- NRCan Funding Agency
- Larry McClung of Leidos Lead on simulations
- o Leigh St. Hilaire of STEP Project manager
- o Gil Amdurski of STEP Technician on project













References

[1] Module spec sheet screenshot from REC Solar; accessed online 05/07/2014 http://www.solarelectricsupply.com/solar-panels/rec-solar-modules

[2] B. Herteleer, J. Cappelle and J Driesen. "Quantifying low-light behaviour of photovoltaic modules by identifying their irradiance dependent efficiency from data sheets," in 27th EU PVSEC.

